

DSG ChargePoint+

DSG Wall Box

Model: DSG-1130 Series

Output Power: 11kW/22kW



Item	Description	
General Information		
Output Power	11kW	22kW
Input Rating	380V Ac 10%, 50/60Hz, 3P+N+PE	
Power Factor	≥ 0.99 Full Load	
Efficiency	$\geq 95\%$ Full Load (Peak)	
Grid Type	TN-S, TN-C, TN-C-S, TT	
Output Interface	Type 2	
Material	ABS + PC	
Output Current	$\leq 16A$ Type 2	$\leq 32A$ Type 2
Color	White	
Charging Mode	Plug & Charge, Rfid Card, APP	
Leakage Protection	Type B. AC (30mA) & DC (6mA)	
Intelligent Charging	-	
User Interface		
Display	4.3"	
Charging	Emergency Stop Button, Led Indicator	
Support Language	English	
Network Interface	BT, Wi-Fi	
Connectivity	2.4835~2.400GHz, Wi-Fi IEEE 802.11b/g/n, Bluetooth 4.2	
APP	Available	
Environmental		
Operating Temperature	-30°C to + 50°C	
Storage Temperature	-40°C to + 70°C	
Humidity	5% to 95% no condensation	
Mechanical		
IP Rating	IP65	
IK Rating	IK10	
Certificate	TUV, CE, CB	
Cooling	Natural cooling	
Charging Cable Length	Type2, 5m or 7m (optional)	
Dimensions (W*H*D)	230x280x90mm	

DSG ChargePoint+

Package Dimension (L*W*H) mm	450*450*180mm
Net Weight	5kg
Installation	Columnar, Wall-mounted