

Model	TA-DC-80FD	TA-DC-120FD	TA-DC-150FD	TA-DC-180FD	TA-DC-240FD
Output Power	80KW	120KW	150KW	180KW	240KW
Output Voltage	200-1000V				
Output Current	200A	0-250A			
Frequency	50/60 Hz				
Input Current	125A	190A	230A	285A	400A
Input Voltage	AC380V±20%				
Gun quantity	ONE / TWO(CCS-1/CCS-2/CHAdeMO/GBT)				
Charging way	Quickor Slowcharge automatic switch				
charging mode	SWIPEARD / APP / MANUAL				
Display	7"Color Touch Screen				
Network connection	Standard configuration :CAN/485/ Ethernet Selective configuration: GPRS/4G				
Weight	200KG	230KG	310KG	320KG	320KG
Operating Temperature	-20C to +50°C				
Altitude	2000M				
IP LEVEL	IP54				
Working Relative Humidity	RH≤95%				
Input cablelength	0M(Customization Acceptable)				
Gun cableLength	5M(Customization Acceptable)				
Interface Standard	CCS CHADEMO GB/T				
Charging protocol	GBT27930/CHADEMO 2.0/ DIN 70121 OCPP 1.6(JSON)/ISO 15118				
Dimension(mm)	730*500*1700				